## Z 182



## **Features**

- Female connector M23 with screwable nut
- With or without cable (shielded) in different lengths
- Cable version: shield is placed onto the connector housing

Part number		
Z 182.001	Female connector M23, 12-pin, less cable (incr.)	
Z 182.003	Female connector M23, 12-pin, 2 m (incr.)	
Z 182.005	Female connector M23, 12-pin, 5 m (incr.)	
Z 182.007	Female connector M23, 12-pin, 10 m (incr.)	
Z 182.M08	Female connector M23, 12-pin, 8 m (incr.)	


## Suitable for

G0A2H, G0L2H, G0M2H, GA240, GA241, GBA2H, GBA2S, GBA2W, GM400, GM401, GXA2S, GXL2S, GXL2W, GXM2S

Technical data			
Cable length	2 m, 5 m, 8 m, 10 m (further length upon request)		
Cable type	LiYCY (TP) 6x2x0.14 mm <sup>2</sup> (shielded, twisted pair)		
Bending radius	6 x cable diameter		
Outer diameter	7.1 mm		
Operating temperature	-40+80 °C		
Material	Cable jacket: PVC grey		

Terminal assignment		
Connector	Core colour	
Pin 1	brown	
Pin 2	white	
Pin 3	blue	
Pin 4	green	
Pin 5	grey	
Pin 6	yellow	
Pin 7	red	
Pin 8	red/blue	
Pin 9	pink	
Pin 10	violet	
Pin 11	black	
Pin 12	grey/pink	
	·	

## **Dimensions**



1